

Name _____ year 197__ 23 or 26 Rally: Yes___ or No ___

License _____ State ____

Please fill in the Tire Seminar Information and mail it in even if you are not coming to the rally. It has two purposes, 1) to assist the Michelin Tire Engineer in his presentation and to answer member questions, and 2) publish a Seminar summary for the GMCWS web page, which will also include a summary of this data and rally weigh-in results. The goal is to provide GMC owners with tire safety information and replacement criteria.

1971-1975 GMC Motorhomes had 8.75 16.5 D rated bias ply, tread fabric/sidewall fabric (F/F) tires with steel rims. In 1976, optional 8.75R 16.5 D rated radial tires and wheels stamped "RADIAL" on the outer rim were phased in. Bias ply tires & wheels remained available thru 1978. Radial tires exert higher wheel loads that can crack a non-radial rim, resulting in leaks and tire failure. 16" Alcoa Classic wheels and LT225_75R16 D or E tires of fabric/steel (F/S) or steel/steel (S/S) are upgrades. Cinnabar recommends E rated (S/S) radial tires @ 80 psi for all radial wheels. Wheel: Steel = S, Steel "RADIAL" = SR, Alcoa classic = AC, Other = O, D= Drivers side, P=Pass side, F=Front, M=Middle, R=Rear DOT #: Last digits = mfg date. First two numbers= week, last number(s)= year 1980's =WWY, 1990's=WWY <|, 2000's =WWYY

Wheel Tires: Brand name/Style	Size & load range	DOT #	F/S or S/S	PSI
DF				
DM				
DR				
PF				
PM				
PR				

"Truck ruts" sensitivity 0-10 (10 = high) _____ Suspension modifications: _____

Question for Michelin Tire Engineer to answer at Seminar: _____

